

## CG26-2.92-J-141-XXX



2.92J-141

### Configuration

|                     |                             |
|---------------------|-----------------------------|
| Connector 1         | 2.92 Male                   |
| Connector 2         | NA#                         |
| Connector Body      | Stainless Steel Passivation |
| Connector Conductor | Beryllium Copper, Gold      |
| Insulation          | PEI                         |
| Cable Type          | Semi-rigid Cable            |
| Cable Diameter      | 141Cable                    |

### Electrical Specifications

|                                    |                     |
|------------------------------------|---------------------|
| Impedance                          | 50Ω                 |
| Frequency Range                    | DC to 26GHz         |
| Insertion Loss                     | <1.4 dB/0.5m,DC-26G |
| VSWR (Voltage Standing Wave Ratio) | ≤1.35, DC to 26GHz  |
| Dielectric withstand Voltage       | 500 V rms           |

### Mechanical Properties

|                 |            |
|-----------------|------------|
| Mechanical Life | 500 cycles |
| Bending Radius  | 5mm        |

### Environment Data

|                     |              |
|---------------------|--------------|
| Working Temperature | -55℃ ~ +125℃ |
|---------------------|--------------|

### Order Information

| P/N                  | Product Description                        |
|----------------------|--------------------------------------------|
| CG26--2.92-J-141-30  | Semi-rigid Cable, 2.92J 26GHz,Length 30cm  |
| CG26--2.92-J-141-XXX | Semi-rigid Cable, 2.92J 26GHz,Length XXXcm |