


CA50-2.4-J/1.85-K-22-XXX



Configuration

Connector 1	2.4mm Male
Connector 2	1.85mm Female
Connector Body	Stainless Steel Passivation
Connector Conductor	Beryllium Copper, Gold
Insulation	PEI
Cable Type	Low Loss Stable Phase Test Cable
Cable Diameter	2.2mm

Electrical Specifications

Impedance	50Ω
Frequency Range	DC to 50GHz
Insertion Loss	<6.02dB/m,DC-50G
VSWR	≤1.30, DC to 50GHz
Dielectric withstand Voltage	500 V rms
Mechanical Phase Stability	TBD
Amplitude Stability	+0.05dB Max.
Different Cable Phase Match	±8 Degree Max.

Mechanical Properties

Mechanical Life	500 cycles
Bending Radius	26mm

Environment Data

Working Temperature	-55℃ ~ +125℃
---------------------	--------------

Order Information

P/N	Product Description
CA50-2.4-J/1.85-K-22-030	Low Loss Stable Phase Test Cable, 2.4(M) to 1.85(K),50GHz,Length 30cm
CA50-2.4-J/1.85-K-22-XXX	Low Loss Stable Phase Test Cable, 2.4(M) to 1.85(K),50GHz,Length XXXcm